


# CORE CUTTERS

At Nicely, we prioritize delivering exceptional service to support our clients' success. Our dedicated technical team establishes direct connections with customers, providing comprehensive training and expert guidance to empower them in maximizing production capabilities.

With our on-site service team and flexible remote support, Nicely is always ready to provide prompt, professional, and reliable assistance to resolve any operational issues, minimizing downtime.

At Nicely, we recognize the importance of uptime and efficiency for customers. That's why we continuously strive for excellence through innovation and improvement. Choose Nicely, Experience unparalleled customer support that drives your success forward.



[Learn More](#)

# EG-NC601

Semi-Automatic Core cutters

## APPLICATIONS

- 3" paper tube
- 6" paper tube
- other sizes are available upon request

**NICELY**

[sales@nicely.com.tw](mailto:sales@nicely.com.tw) / [+886-3-3249020](tel:+886-3-3249020) / [www.nicely-slitte.com](http://www.nicely-slitte.com)

NICELY MACHINERY DEVELOPMENT CO., LTD



# EG-NC601

## SEMI-AUTOMATIC CORE CUTTERS

EG-NC601 automatic core cutter is equipped with a range of automatic features, streamlining the cutting process and ensuring optimal performance. Its user-friendly interface allows for quick and easy settings adjustment, accommodating various core diameters and wall thicknesses. Our EG-NC601 automatic core cutter can be customized with or without a loading device to accommodate different customer requirements.

## CORE CUTTERS

### Optional Features

- Core loading ramp
- Different tube size other than 3" & 6" is quoted at request



### Standard Features

- Loading tube rack
- Programable production receipts
- Pneumatic cutting tool
- Accommodate core clamp and core module. (3" & 6")
- Core collector
- Lift-type safety cover with windows

### General Specifications

Max. Parent core length	2000 – 6800 mm
Paper tube I.D	76 – 152.2 mm
Paper tube O.D	102 – 182.4 mm
Core thickness	Max. 20 mm
Cutting length	Min. 10 mm
Other specification is offered at request.	

